



KOSTER Silicone Paint White

Technical Data Sheet P 260 010

Issued: 01-07-19

Silicone resin paint for exterior or interior rendered and mineralplaster covered surfaces

Features

KOSTER Sllicone Paint White is a matte, water-soluble, capillary-hydrophobic façade paint based on silicone resins with special bonding enhancers and special non-wetting-surface effect. It dries to a smooth finish and has a highly vapor-permeable surface. Because of its excellent water vapor permeability, it is suited for outer coloring of KOSTER Restoration Plaster systems. The paint is also suited for exposed masonry made of limestone, brick, and other mineral substrates. Applied in the preservation of historical monuments, KOSTER Silicone Paint White offers optimal protection of the building because of its low water absorption and its high water vapor permeability. KOSTER Silicone Paint White is also suitable for interior use.

Fields of Application

KOSTER Silicone Paint White is designed as a durable paint coating on smooth and rough renders and plasters.

Substrate

The substrate must be level, sound, clean and dry. All loose particles must be removed. KOSTER Silicone Paint must only be applied after the substrate has fully dried. If necessary, a preliminary test area should be coated before application.

Application

Mix well before application. Apply using a brush, roller, or suitable spraying equipment. For priming, dilute KOSTER Silicone Paint White with up to 10% water. Apply the main coat after the primer has fully dried. Do not apply the paint if either the outside temperature or the substrate temperature is below 40°F, or if the surface to be painted has been heated by the sun. Drying time at 70°F and 65% RH is approx. 12 hours. Lower temperatures and higher humidity may prolong drying time.

Coverage

Approx. 200 sq ft/gal per coat

Cleaning

Clean tools with water immediately after use.

Packaging

P 260 010 2.64 gallon bucket

Storage

Store in a cool, dry place. Protect from freezing. In original sealed packaging, it can be stored for 1 year.

Safety

Consult Safety Data Sheet. Always wear proper personal protective equipment when handling this product.

Limited Warranty

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the products data sheet. KOSTER covenants that in the event any of its products fail to meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The user must determine if the product is suited for the intended use and the user must bear the risks and liabilities associated with it.

Related products

KOSTER Restoration Plaster White Art.-Nr. M 662 025

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised; all previous versions are invalid.