



KOSTER KB-FIX 1

Technical Data Sheet C 511 015

Issued: 01-03-17

Fast-setting cement for rapid installations

Features

KOSTER KB-Fix 1 is an extremely fast-setting waterproof and weatherproof cement for rapid installations.

Technical Data

Starts to set After approx. 60 seconds Application of next layer After approx. 2 hrs

Fields of Application

KOSTER KB-Fix 1 is intended for rapid filling of holes and cracks in plaster and masonry, for sealing pipe penetrations, for anchoring wall anchors, anchor fittings, brackets of roof gutters and down pipes, handrails, grates, radiators, as well as for rapid repairs at home. KOSTER KB-Fix 1 is suitable for both interior and exterior applications.

Substrate

Remove any loose particles. Wet holes or cracks with water, insert parts to be anchored.

Application

Mix 3 parts of KOSTER KB-Fix 1 with 1 part of water into a stiff, viscous mortar. When doing sealing work or repairing larger areas, press the mortar into place using a board or trowel until it has set. Do not prepare more material than can be applied before the setting time. In cold weather, mix KOSTER KB-Fix 1 with warm water (approx. 70°F).

Coverage

Approx. 0.3 cu ft per 33 lb bucket.

Cleaning

Clean tools immediately after use with water.

Packaging

C 511 015 33 lb bucket

Storage

Store the material in a dry, frost-free environment. In originally sealed packaging, it canbe stored for approx. 6 months.

Safety

Consult Safety Data Sheet. Always wear proper personal protective equipment when handling this product.

Warranty

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the products data sheet. KOSTER covenants that in the event any of its products fail to meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for

any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The user must determine if the product is suited for the intended use and the user must bear the risks and liabilities associated with it.

Related products

KOSTER KB-FIX 5 Art.-Nr. C 515 015

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised; all previous versions are invalid.