



KOSTER Turbo Super Plasticizer

Superplasticizer for KOSTER Turbo System

Features

KOSTER Turbo Super Plasticizer is an additive for the KOSTER Turbo System to adjust the consistency of the KOSTER Turbo System to individual jobsite requirements.

Fields of Application

KOSTER Turbo Super Plasticizer adjusts the flow of KOSTER Turbo Mortar F and KOSTER Turbo Mortar M in areas where more flow or self leveling consistency is desired:

- Filling formwork without compacting
- Forms and holes in concrete floors

Substrate

The substrate must be sound, solid, and free of bond inhibiting agents such as grease, oil, laitance, loose particles, dust, or form release oil. The substrate can be prepared by shotblasting, grinding, brushing, or sweeping. KOSTER Turbo Super Plasticizer is only for use with the KOSTER Turbo System.

Application

Mix one 55 lb bag of KOSTER Turbo Mortar F/M with 4.2 qts of clean water. After mixing the KOSTER Turbo Mortar, add KOSTER Turbo Super Plasticizer slowly and evenly while mixing. Mix until the desired consistency is reached. If a self-leveling consistency is desired, up to 0.5 qts of water can be added.

Aftertreatment

If necessary, cure the installed material by covering with polyethylene sheeting.

Coverage

One pack per 55 lb bag KOSTER Turbo Mortar Fine/Medium

Cleaning

Clean tools immediately after use with fresh water.

Packaging

C 717 065 65 gram bag

Storage

Store in a cool, dry place.

Safety

Consult Safety Data Sheet. Always wear proper personal protective equipment when handling this product.

Limited Warranty

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the products data sheet. KOSTER covenants that in the event any of its products fail to

meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The user must determine if the product is suited for the intended use and the user must bear the risks and liabilities associated with it.

Related products

KOSTER Turbo Mortar F
KOSTER Turbo Mortar M

Art.-Nr. C 516 025
Art.-Nr. C 517 025

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised; all previous versions are invalid.