



KOSTER Color Quartz

Decorative color coated quartz for broadcasting into KOSTER epoxy resins

Features

KOSTER Color Quartz is composed of fine uniformly shaped and sized quartz granules. This unique product is brilliantly color-coated with an advanced resin system and high-quality color pigments to provide optimal durability and extreme performance in the most demanding environments. In addition to their superior resilience to harsh chemicals and UV rays, KOSTER Color Quartz can be applied to achieve many different textures to minimize slips and falls.

Technical Data

	Q40	Q25
Grain size	40 mesh	25 mesh
Grain shape	Spherical	Angular

Fields of Application

Use KOSTER Color Quartz to coordinate your floors and walls with any decor. Our extensive line of colors give you the ability to custom design blends to match any color scheme.

Application

KOSTER Color Quartz is broadcast by hand into the fresh coat of KOSTER MPE to achieve a uniform distribution. KOSTER Color Quartz should be thrown upwards and not directly into the fresh surface. Prepared areas should always be completely treated in one work step to ensure a homogenous appearance.

Coverage

Grade	Full Coverage/Double broadcast
Q40	0.5 - 1 lb/sq ft
Q25	1-2 lb/sq ft

Packaging

CT 486 050	50 lb bag
------------	-----------

Storage

Store in a cool, dry area. If stored in originally sealed bags, material can be stored for 2 years.

Safety

Consult Safety Data Sheet. Always wear proper personal protective equipment when handling this product.

Limited Warranty

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the products data sheet. KOSTER covenants that in the event any of its products fail to meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for

any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The user must determine if the product is suited for the intended use and the user must bear the risks and liabilities associated with it.

Related products

KOSTER MPE
KOSTER MPE-F
KOSTER MPE-Color
KOSTER MPE-F-Color
KOSTER UTC
KOSTER UTC-Color
KOSTER UTC-LT
KOSTER UTC-LT-Color
KOSTER ES
KOSTER Color Chips

Art.-Nr. CT 261
Art.-Nr. CT 262
Art.-Nr. CT 263
Art.-Nr. CT 264
Art.-Nr. CT 321
Art.-Nr. CT 322
Art.-Nr. CT 323
Art.-Nr. CT 324
Art.-Nr. CT 366
Art.-Nr. CT 429

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised; all previous versions are invalid.