



# KOSTER Adhesion Promoting Additive

## Adhesion promoting additive for KOSTER epoxy and urethane coatings

### Features

KOSTER Adhesion Promoting Additive is a silane polymer liquid additive that improves the adhesion properties of KOSTER epoxy and urethane coatings to certain substrates. The addition of KOSTER Adhesion Promoting Additive is only needed in the coat that will bond directly to the substrate in question.

### Fields of Application

Adding KOSTER Adhesion Promoting Additive to a KOSTER epoxy coating is highly recommended when applying a KOSTER epoxy coating or epoxy flooring system over ceramic tile, quarry tile, brick pavers, or existing epoxy or urethane coatings.

### Application

Add 3 fl.oz of KOSTER Adhesion Promoting Additive per gallon of mixed KOSTER MPE, ES or UTC. Mix the A and B component of the material, and add the additive into the mix. Mix the material with the additive for the time recommended on the respective data sheet. Once mixed, apply the material immediately.

### Coverage

3 fl.oz per gallon of mixed KOSTER MPE, ES or UTC.

### Packaging

CT 761 001 1 gal can

### Storage

Store dry.

### Safety

Consult Safety Data Sheet. Always wear proper personal protective equipment when handling this product.

### Limited Warranty

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the products data sheet. KOSTER covenants that in the event any of its products fail to meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The user must determine if the product is suited

for the intended use and the user must bear the risks and liabilities associated with it.

### Related products

KOSTER MPE	Art.-Nr. CT 261
KOSTER MPE-F	Art.-Nr. CT 262
KOSTER MPE-Color	Art.-Nr. CT 263
KOSTER MPE-F-Color	Art.-Nr. CT 264
KOSTER UTC	Art.-Nr. CT 321
KOSTER UTC-Color	Art.-Nr. CT 322
KOSTER UTC-LT	Art.-Nr. CT 323
KOSTER UTC-LT-Color	Art.-Nr. CT 324
KOSTER ES	Art.-Nr. CT 366
KOSTER Color Chips	Art.-Nr. CT 429
KOSTER Color Quartz	Art.-Nr. CT 486 050
KOSTER Skid-Resistant Broadcast-Medium	Art.-Nr. CT 486 055
KOSTER Skid-Resistant Broadcast-Coarse	Art.-Nr. CT 487 055
KOSTER TA Fiber	Art.-Nr. CT 755 044
KOSTER TA Fumed Silica	Art.-Nr. CT 756 053
KOSTER Abrasion Resistant Additive	Art.-Nr. CT 757 007
KOSTER Anti-Microbial Additive	Art.-Nr. CT 759 001
KOSTER Fisheye Eliminating Additive	Art.-Nr. CT 760 010
KOSTER Slip-Resistant Additive	Art.-Nr. CT 762 001
KOSTER Matte Additive	Art.-Nr. CT 763 001

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised; all previous versions are invalid.