



KOSTER KB-Pur Cleaner

Organic cleaning agent for polyurethane spills

Features

KOSTER KB-Pur Cleaner is designed for removing non-reacted polyurethane.

Application

Treat the affected areas with KOSTER KB-Pur Cleaner until residue is removed.

Packaging

IN 900 010 2.64 gal jerrycan

Storage

In original sealed packages, it may be stored for 2 years.

Safety

Consult Safety Data Sheet. Always wear proper personal protective equipment when handling this product.

Limited Warranty

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the products data sheet. KOSTER covenants that in the event any of its products fail to meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The user must determine if the product is suited for the intended use and the user must bear the risks and liabilities associated with it.

Related products

KOSTER UC 100	Art.-Nr. CT 251 026
KOSTER UC 200	Art.-Nr. CT 252 020
KOSTER UC 300	Art.-Nr. CT 253 010
KOSTER UTC	Art.-Nr. CT 321
KOSTER UTC-Color	Art.-Nr. CT 322
KOSTER UTC-LT	Art.-Nr. CT 323
KOSTER UTC-LT-Color	Art.-Nr. CT 324
KOSTER IN 1	Art.-Nr. IN 110
KOSTER 2 IN 1	Art.-Nr. IN 201
KOSTER IN 2	Art.-Nr. IN 220
KOSTER IN 3	Art.-Nr. IN 230
KOSTER IN 5	Art.-Nr. IN 250
KOSTER IN 7	Art.-Nr. IN 270

KOSTER PUR Gel
KOSTER Gel Pump
KOSTER 1C Injection Pump
KOSTER Footpump

Art.-Nr. IN 285
Art.-Nr. IN 928 001
Art.-Nr. IN 929 001
Art.-Nr. IN 958 001

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised; all previous versions are invalid.