



# KOSTER Glass Fiber Mesh

## Fiberglass fabric for reinforcing coatings

### Features

KOSTER Glass Fiber Mesh is a fiberglass fabric with extremely high tear resistance.

### Technical Data

Color	White
Weight	Approx. 0.015 lb/sq ft
Tear Resistance	Approx. 115 lbf/in
Mesh size	15/64 X 9/32-in

### Related products

KOSTER BD 50  
 KOSTER Dachflex  
 KOSTER NB 4000  
 KOSTER KBE Liquid Film  
 KOSTER Deuxan Professional

Art.-Nr. B 290 010  
 Art.-Nr. R 260 020  
 Art.-Nr. W 236 020  
 Art.-Nr. W 245  
 Art.-Nr. W 256 032

### Fields of Application

KOSTER Glass Fiber Mesh is a reinforcing fabric for reinforcing KOSTER KBE Liquid Film, KOSTER Bikuthan 1C and 2C, KOSTER Deuxan Professional and 2C, KOSTER BD 50, and KOSTER Dachflex. KOSTER Glass Fiber Mesh is designed for use in areas which are exposed to pressurized water, areas in danger of cracking, and over connections, transitions, and fillets.

### Application

Follow application instructions of KOSTER coating being installed. Embed KOSTER Glass Fiber Mesh into the fresh first layer. After the first layer has cured, cover with subsequent layers. Installed sheets of KOSTER Glass Fiber Mesh must overlap each other by at least 2 inches.

### Packaging

W 411 033	13 in x 328 ft roll (355 sq ft)
W 411 100	3.3 ft x 328 ft (1076 sq ft)

### Safety

Consult Safety Data Sheet. Always wear proper personal protective equipment.

### Warranty

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the products data sheet. KOSTER covenants that in the event any of its products fail to meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The user must determine if the product is suited for the intended use and the user must bear the risks and liabilities associated with it.

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised; all previous versions are invalid.