



KOSTER EasyCove System

Easy to install, pre-formed floor to wall cove base system

Features

The KOSTER EasyCove System is a highly engineered cove base molding designed for the resinous flooring industry. Its patented design is easily coated, and provides numerous benefits over traditional hand troweled and existing cove moldings.

Technical Data

Height:	4 or 6 inches
Cove radius:	1 "
Base portion thickness:	Approx 1/4"
Length:	48"
Total distance out from wall:	≤ 1 1/4"
Packaging:	(15) 4' sections per box

Substrate

The substrate should be solid, and ideally prepared to the original structural material. Whenever applying EasyCove over a previously painted surface, the bond will only be as good as the coating that EasyCove is adhered to.

Application

KOSTER EasyCove should be applied at operating temperature of the room whenever possible. Once EasyCove is removed from the box, it should be laid in a warm area, completely flat, to make sure there are no kinks or deformities. A heat gun is helpful to help the material relax. Heat can also be used to accelerate the adhesive.

Lay out EasyCove sections before installation. Adhesive can be used to join adjacent pieces to one another for monolithic installation. Cove base can be mitered at corners for seamless installation.

Once the substrate is prepared, apply a bead of KOSTER EasyCove Adhesive to both bond channels on the back of the cove base, as well as where the cove anchor meets the wall and floor. The purpose of the bead is to create a waterproof seal between the adhesive and the EasyCove cove anchor. Failure to have a consistent bead may allow moisture to intrude, so this step is very critical. Tilt EasyCove up into position and apply even pressure using a soft cotton towel to make sure cove is completely pressed against the wall and floor.

Coatings can be installed as soon as the EasyCove has been installed

Cleaning

Clean tools immediately after use with xylene or a similar solvent. Store and dispose of cleaning solvent and rags according to jobsite rules and applicable regulations.

Storage

Store in original container away from sunlight between 50°F - 90°F.

Safety

Consult Safety Data Sheet. May cause irritation to eyes or skin. Avoid contact with eyes or prolonged contact with skin. In case of eye

contact, flood with clean water and seek medical attention. In case of skin contact, wash area with soap and water. Do not use solvents on skin.

Warranties

KOSTER warrants that its product shall be in accordance with the specifications published in the current revision of the product data sheet. KOSTER covenants that in the event any of its products fail to meet their published specifications, KOSTER shall replace those products proved to be defective. KOSTER shall not be responsible for any incidental or consequential damages due to the breach of its warranties. Notwithstanding the foregoing, KOSTER's sole liability hereunder shall not exceed the cost of the defective product originally purchased. EXCEPT AS SET FORTH ABOVE, KOSTER MAKES NO OTHER WARRANTIES EXPRESS OR IMPLIED AND MAKES NO WARRANTY AS TO THE MERCHANTABILITY OR FITNESS OF THE PRODUCT FOR A PARTICULAR PURPOSE. THERE ARE NO WARRANTIES WHICH EXTEND BEYOND THE DESCRIPTION ON THE FACE HEREOF. The user must determine if the product is suited for the intended use and the user must bear the risks and liabilities associated with it.

The information contained in this technical data sheet is based on the results of our research and on our practical experience in the field. All given test data are average values which have been obtained under defined conditions. The installer is responsible for the correct application taking into consideration the specific conditions of the construction site and the final results of the construction process. This may require adjustments to the recommendations given here for standard cases. Specifications made by our employees or representatives which deviate from the specifications contained in any Company literature may not be relied upon in the absence of written confirmation from the Company. The installer must comply with all testing, technical requirement, guidelines, and industry customs at all times. The terms, conditions, and limitations contained in the written warranty for the product controls over the specifications contained herein. This guideline has been technically revised; all previous versions are invalid.