## **DEW POINT CALCULATION CHART**

**Ambient Air Temperature- Fahrenheit** 

| Relative | 20 | 30 | 40 | 50 | 60 | 70 | 80 | 90 | 100 | 110 | 120 |
|----------|----|----|----|----|----|----|----|----|-----|-----|-----|
| Humidity |    |    |    |    |    |    |    |    |     |     |     |
| 90%      | 18 | 28 | 37 | 47 | 57 | 67 | 77 | 87 | 97  | 107 | 117 |
| 85%      | 17 | 26 | 36 | 45 | 55 | 65 | 75 | 84 | 95  | 104 | 113 |
| 80%      | 16 | 25 | 34 | 44 | 54 | 63 | 73 | 82 | 93  | 102 | 110 |
| 75%      | 15 | 24 | 33 | 42 | 52 | 62 | 71 | 80 | 91  | 100 | 108 |
| 70%      | 13 | 22 | 31 | 40 | 50 | 60 | 68 | 78 | 88  | 96  | 105 |
| 65%      | 12 | 20 | 29 | 38 | 47 | 57 | 66 | 76 | 85  | 93  | 103 |
| 60%      | 11 | 19 | 27 | 36 | 45 | 55 | 64 | 73 | 83  | 92  | 101 |
| 55%      | 9  | 17 | 25 | 34 | 43 | 53 | 61 | 70 | 80  | 89  | 98  |
| 50%      | 6  | 15 | 23 | 31 | 40 | 50 | 59 | 67 | 77  | 86  | 94  |
| 45%      | 4  | 13 | 21 | 29 | 37 | 47 | 56 | 64 | 73  | 82  | 91  |
| 40%      | 1  | 11 | 18 | 26 | 35 | 43 | 52 | 61 | 69  | 78  | 87  |
| 35%      | -2 | 8  | 16 | 23 | 31 | 40 | 48 | 57 | 65  | 74  | 83  |
| 30%      | -6 | 4  | 13 | 20 | 28 | 36 | 44 | 52 | 61  | 69  | 77  |

## SURFACE TEMPERATURE AT WHICH CONDENSATION OCCURS

**DEW POINT:** Temperature at which moisture will condense on the surface. No coatings should be applied unless surface is a minimum of 5 degrees above this point. Temperature must be maintained during curing, or Temperature should be steady and falling, but never rising.

**EXAMPLE**: If air temperature is 70°F and relative humidity is 65%, the dew point is 57°F. No coating should be applied unless the surface temperature of the concrete slab is 62°F minimum.